

## WEST Search History

DATE: Monday, October 10, 2005

Hide?	<u>Set</u> <u>Name</u>	<u>Query</u>	<u>Hit</u> <u>Count</u>
		<i>DB=PGPB,USPT,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ</i>	
<input type="checkbox"/>	L6	measuring and displacement and L4	96
<input type="checkbox"/>	L5	measuring displacement and L4	5
<input type="checkbox"/>	L4	mobile robot and L3	884
<input type="checkbox"/>	L3	(robot\$6 or articulat\$3 or automat\$6 or autonomous\$2 or CNC or machine\$2 or mechanical device or mechan\$6 or servomechan\$4) and (camera or video or image sensor)	447119
<input type="checkbox"/>	L2	navigat\$5 and kalman filter and correct\$4 and (radio or wave) or frequenc\$3	1821231
<input type="checkbox"/>	L1	10/697282	1

END OF SEARCH HISTORY



 **Search Result - Print  
Format**

[< Back to Previous Page](#)

**Key:** IEEE JNL = IEEE Journal or Magazine, IEE JNL = IEE Journal or Magazine, IEEE CNF = IEEE Conference, IEE CNF = IEE Conference, IEEE STD = IEEE Standard

**1. A kinematic-independent dead-reckoning sensor for indoor mobile robotics**

Bonarini, A.; Matteucci, M.; Restelli, M.;  
Intelligent Robots and Systems, 2004. (IROS 2004). Proceedings. 2004  
IEEE/RSJ International Conference on  
Volume 4, 28 Sept.-2 Oct. 2004 Page(s):3750 - 3755 vol.4  
IEEE CNF

**2. Computation of shape through controlled active exploration**

Smith, C.E.; Papanikolopoulos, N.P.;  
Robotics and Automation, 1994. Proceedings., 1994 IEEE International  
Conference on  
8-13 May 1994 Page(s):2516 - 2521 vol.3  
IEEE CNF

Indexed by  


© Copyright 2005 IEEE – All Rights Reserved



[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#) <sup>New!</sup> [more »](#)

robot "measuring displacement" camera image

[Advanced Search](#)  
[Preferences](#)

**Web Results 1 - 10** of about **49** for **robot "measuring displacement" camera image motion**. (0.34 seconds)

Tip: Looking for pictures? Try [Google Images](#)

Sponsored Links

Vision-Based Sensor for Real-Time Measuring of Surface Traction Fields

Figure 4 shows an **image** captured by the CCD **camera** and sent directly to a PC. ... Similarly, to operate dexterously, **robots** must sense both the grasping and ...  
doi.ieeecomputersociety.org/10.1109/MCG.2005.27 - [Similar pages](#)

Displacement Sensors

MICRO-EPSILON is an authority in providing **displacement** solutions.  
micro-epsilon.com

Briefs: Photonics

Interferometer for **Measuring Displacement** to Within 20 pm NPO21221 ...  
MFS31718; Custom Software for Infrared **Camera Image** Acquisition and Control INDIGO0403 ...  
www.nasatech.com/Briefs/photonics.html - 68k - [Cached](#) - [Similar pages](#)

Optical Measurement Systems for Industrial Inspection III ...

... grid is the grid on the **robot** marks ... structured light system and the CCD **camera** takes **images** ... the most powerful methods for **measuring displacement** deformation or ...  
www.spie.org/Conferences/Programs/03/eom/conferences/index.cfm?fuseaction=5144 - 101k - Supplemental Result - [Cached](#) - [Similar pages](#)

[PDF] Date:

File Format: PDF/Adobe Acrobat - [View as HTML](#)  
... DMD Reflection-Type CCD **Camera** Motoharu Fujigaki ... 211 Design Of Micro **Robots** With Microgrippers ... Laser Interferometry Method For **Measuring Displacement** Field Of ...  
www.icem04.org/ Detailed%20Technical%20Programme%20(12Oct04).pdf - Supplemental Result - [Similar pages](#)

Residual Waste Volume Measurement for Hanford Underground Storage ...

A point in the **image** of one **camera** must be identified and located. The same point must be located in the **image** of the second **camera**. ...  
www.tanks.org/ttgdoc/whcsdwm180.htm - 47k - [Cached](#) - [Similar pages](#)

Research centers, Faculty of Mechanical Eng., Technion

**Motion** and interaction of inertial particles in the turbulent atmosphere ...  
New **robot** structures, parallel **robots**, miniature **robots**, medical **robots**, ...  
meeng.technion.ac.il/Research/Centers/centers.html - 38k - [Cached](#) - [Similar pages](#)

[PS] Hough Localization for Mobile **Robots** in Polygonal Environments ...

File Format: Adobe PostScript - [View as Text](#)  
sponds to errors in the calibration of the **camera**. ffl **robot** bumps: random movements of ... These samples are generated during **robot motion** using odometry ...  
www.dis.uniroma1.it/~iocchi/publications/iocchi-RAS02.ps.gz - [Similar pages](#)

**[PDF] Simulating self motion II: A virtual reality tricycle**File Format: PDF/Adobe Acrobat - [View as HTML](#)

ongoing pose of a mobile **robot** cannot be estimated using internal sensors only, and ... is the current state vector ( $u, v$  **image** coordinates) and  $v$  ...  
[www.cs.yorku.ca/~jenkin/papers/2002/vr2.pdf](http://www.cs.yorku.ca/~jenkin/papers/2002/vr2.pdf) - [Similar pages](#)

**[PDF] Salient Design Considerations**File Format: PDF/Adobe Acrobat - [View as HTML](#)

**motion** attached to the bottom hull and two for horizontal **motion** located on the ... An integral part of the vision system is the RHP-320WP infrared **camera** ...


[www.auvsi.org/competitions/2000/Papers/StevensPaper.pdf](http://www.auvsi.org/competitions/2000/Papers/StevensPaper.pdf) - [Similar pages](#)**[PDF] Vision-Based Sensor for Real- Time Measuring of Surface Traction ...**

File Format: PDF/Adobe Acrobat

ment of  $B$  to a new configuration describes the **motion**, which we define as.  
 $u(x, t) = \kappa(x, t) - x$  ... **camera image**. Given applied traction field  $\Phi$ , we used ...

[ieeexplore.ieee.org/iel5/38/30111/01381228.pdf?arnumber=1381228](http://ieeexplore.ieee.org/iel5/38/30111/01381228.pdf?arnumber=1381228) -[Similar pages](#)

Goooooogle ►

Result Page: [1](#) [2](#) [3](#) [4](#) [5](#) [Next](#)Free! Instantly find your email, files, media and web history. [Download now.](#) [Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#)[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2005 Google